

TECHNICAL BULLETIN



19 Motivation Dve Wangara, WA, 6065 AUSTRALIA
T +61 8 9302 4000 | FREE 1800 999 196 | F +61 8 9302 5000

ANTIFOAM FG20 DEFOAMING AGENT

MATERIAL & FUNCTION

ANTIFOAM FG20 will eliminate foam in a variety of situations including bottle washing foam suppression, hot water extraction, carpet cleaning machines, foam suppression in recovery tanks, CIP foam control in food industry applications and many more situations where foam control is required.

APPLICATION

ANTIFOAM FG20 should be utilized at concentrations between 0.005% and 0.05% of active component causing foam. Where the quantity of active component generating the foam is not known, then a quantity of **ANTIFOAM FG20** required could vary from 0.01% to 0.2% and trials will need to be undertaken to determine the appropriate rate of addition.

PACKAGING

1 Litre,, 5 Litre & 15 Litre containers.

IMPORTANT NOTICE TO CUSTOMER

*Since the use of this product is beyond the control of either seller or manufacturer, their only obligation shall be to replace any quantity of product which is proven defective. They cannot assume any risk or liability in excess of the purchase price of the product itself, which does not include labour or any consequential damages resulting from the use of this product. Determining the suitability of this product for any intended use shall be solely the responsibility of the user. **ALWAYS TEST FIRST.***