

TECHNICAL BULLETIN



19 Motivation Dve Wangara, WA, 6065 AUSTRALIA
T +61 8 9302 4000 | FREE 1800 999 196 | F +61 8 9302 5000

Page 1 of 2

Date of Issue: 4/4/2016

Last revision: February 2016

File C:\Users\Conrado Concepcion\AppData\Local\Temp\WordHelper\BW2214 - New boiler boilout.docx

BW2214

New Boiler Boilout

Product Description

BW2214 New Boiler Boilout is designed to remove deposits of residual oil, grease and protective coating inherent in manufacturing procedures from the internal surfaces of a new boiler. It is important that these deposits be removed from the heating surfaces since this contamination will lower the heat transfer rate and possibly cause overheating of pressure vessel metal.

Product Benefits.

- Prevents overheating of pressure vessel metal.
- Cost effective
- Maximize heat transfer rate
- Prevents flash Corrosion
- Passivate boiler surfaces

Application

- All new boilers and hot water systems
- Follow manufactures procedures or contact your **ENVIRONEX** water specialist for assistance

Features

- BW2214** is alkaline liquid.
- Excellent dispersion properties.
- Ready to use liquid

Dosage requirements

- Dose 10 liter **BW2214** per 1000 liters of water the boiler holds at steaming level.

Monitoring

- Control Sulfite residues between 20 and 60 ppm in boiler Blowdown.

Handling and Storage.

- Read the label and Material Safety Data Sheet for complete handling information before using this product.
- BW2214** may be stored up to one year.

Quality

- Environex International** is licensed as a Quality Endorsed Manufacturing Company under ISO9001.

TECHNICAL BULLETIN



19 Motivation Dve Wangara, WA, 6065 AUSTRALIA
T +61 8 9302 4000 | FREE 1800 999 196 | F +61 8 9302 5000

Page 2 of 2

Date of Issue: 4/4/2016

Last revision: February 2016

File C:\Users\Conrado Concepcion\AppData\Local\Temp\WordHelper\BW2214 - New boiler boilout.docx

BW2214

Contains <10% Sodium Hydroxide
10-30% Tetrapotassium pyrophosphate

DANGER

Causes severe skin burns and eye damage

Do not breathe mists. Wear protective gloves/ eye protection/ face protection. IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/shower. Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER or doctor/physician. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/ physician.

EMERGENCY INFORMATION: SPILLS: Dam spill. Transfer into drums for disposal. Residues should be neutralised with dilute acid. Additional information is listed in the Material Safety Data Sheet.

IN AN EMERGENCY DIAL 000 POLICE OR FIRE BRIGADE

ENVIRONEX INTERNATIONAL

T: +61 8 9302 4000 E : sales@environex.net.au

F: +61 8 9302 5000 W: www.environex.net.au

FREE 1800 999 196 19 Motivation Drive, Wangara, WA 6065


BW2214 New Boiler Boilout will remove deposits of residual oil, grease and protective coatings from the internal surfaces of a new boiler. Dose 10 L per 1000 L of water the boiler holds at steaming level.



UN 1760 CORROSIVE LIQUID,
N.O.S. (SODIUM HYDROXIDE)
CLASS 8 HAZCHEM 2X PG II

CONTENTS ???? L

BATCH NO. ????????



created by free version of

DocuFreezer