

TECHNICAL BULLETIN



19 Motivation Dve Wangara, WA, 6065 AUSTRALIA
T +61 8 9302 4000 | FREE 1800 999 196 | F +61 8 9302 5000

Page 1 of 2

Date of Issue: 4/4/2016

Last revision: February 2016

File C:\Users\Conrado Concepcion\AppData\Local\Temp\WordHelper\BW2224 - Boiler acid Clean.docx

BW2224 Boiler Acid Clean

Product Description

BW2224 Boiler Acid Clean is designed to remove scale and inorganic sludge from boiler internals without damaging metal surfaces.

Product Benefits.

- Removes built-up scale.
- Dissolves inorganic sludge
- Maximize heat transfer rate
- Fast Acting
- Minimize Boiler downtime

Application

- Use **BW2224** for cleaning of scaled boilers and heat transfer surfaces.
- Follow boiler manufactures procedures or contact your **ENVIRONEX** water specialist for assistance

Features

- Inhibited acid solution.
- Excellent scale removal properties.
- Ready to use liquid.

Dosage requirements

- Mix 1 part of **BW2224** with 20 parts of boiler water capacity.

Monitoring

- Check pH regularly and replace solution if pH is above 4.
- Temperature 50 to 60 °C

Handling and Storage.

- Read the label and Material Safety Data Sheet for complete handling information before using this product.
- BW2224** may be stored up to one year.

Quality

- ENVIRONEX International** is licensed as a Quality Endorsed Manufacturing Company under ISO9001.

TECHNICAL BULLETIN



19 Motivation Dve Wangara, WA, 6065 AUSTRALIA
T +61 8 9302 4000 | FREE 1800 999 196 | F +61 8 9302 5000

Page 2 of 2

Date of Issue: 4/4/2016

Last revision: February 2016

File C:\Users\Conrado Concepcion\AppData\Local\Temp\WordHelper\BW2224 - Boiler acid Clean.docx

BW2224

CONTAINS 260 g/L HYDROCHLORIC ACID

DANGER

May be corrosive to metals. Causes severe skin burns and eye damage. May cause respiratory irritation.

Do not breathe dusts or mists. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/ protective clothing/ eye protection/face protection.

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/physician. Additional information is listed in the Material Safety Data Sheet.

BW2224 is an inhibited acid designed to remove scale and inorganic sludge from boiler internals without damaging metal surfaces.


DIRECTIONS: Dilute 1 part to 20 parts boiler water capacity.



UN 1789 HYDROCHLORIC ACID CLASS 8 HAZCHEM2R PG II

In An Emergency Dial 000 Police or Fire Brigade

BATCH NO. ????????



CONTENTS ???? L

ENVIRONEX INTERNATIONAL

T: +61 8 9302 4000 E : sales@environex.net.au

F: +61 8 9302 5000 W: www.environex.net.au

FREE 1800 999 196 19 Motivation Drive, Wangara, WA 6065