

# TECHNICAL BULLETIN



19 Motivation Dve Wangara, WA, 6065 AUSTRALIA  
T +61 8 9302 4000 | FREE 1800 999 196 | F +61 8 9302 5000

Page 1 of 2

Date of Issue: 4/4/2016

Last revision: February 2016

File C:\Users\Conrado Concepcion\AppData\Local\Temp\WordHelper\BW5354 - Boiler antifoam.docx

## BW5354 BOILER ANTIFOAM

### Product Description

**ENVIRONEX BW5354 BOILER ANTIFOAM** will prevent problems associated with foaming in boilers caused by hydrocarbon contamination and will also allow running at higher cycles.

### Product Features.

- 💧 Prevent foaming caused by contamination.
- 💧 Control foaming caused by increased TDS, SS and Alkalinity
- 💧 FDA Approved

### Product Benefits

- 💧 Prevent condensate contamination due to carry-over
- 💧 Allows higher cycles, thereby:
  - Decrease water consumption
  - Reduce energy costs
  - Lower chemical usage
- 💧 Ready to use liquid

### Application

**BW5354** can be used in all boilers where foaming is suspected or where energy savings is sought.

### Dosage requirements

- 💧 Dose 1-500 ppm **BW5354** based on Feed water flow rate.
- 💧 Dosage will vary based on feed water quality.

### Monitoring

- 💧 Monitor steam quality to ensure no carry-over

### Handling and Storage.

- 💧 Read the label and Material Safety Data Sheet for complete handling information before using this product.
- 💧 **BW5354** may be stored up to one year.

### Quality

- 💧 **ENVIRONEX International** is licensed as a Quality Endorsed Manufacturing Company under ISO9001.

# TECHNICAL BULLETIN



19 Motivation Dve Wangara, WA, 6065 AUSTRALIA  
T +61 8 9302 4000 | FREE 1800 999 196 | F +61 8 9302 5000

Page 2 of 2

Date of Issue: 4/4/2016

Last revision: February 2016

File C:\Users\Conrado Concepcion\AppData\Local\Temp\WordHelper\BW5354 - Boiler antifoam.docx

## **BW5354**

A 20% silicone emulsion

BW 5354 is a boiler antifoam which will prevent problems associated with foaming in boilers caused by hydrocarbon contamination. It will also allow running at higher cycles.

Dose rate 1- 500 ppm based on feed water flow rate.

**FIRST AID:** If poisoning occurs, contact a Poisons Information Centre (Phone Australia 131 126) or a doctor (at once). If swallowed, do NOT induce vomiting, give a glass of water. If in eyes, hold eyes open, flood with water for at least 15 minutes and see a doctor.

**SAFETY DIRECTIONS:** Avoid contact with eyes and skin.

BATCH NO. ????????  CONTENTS ???? L

???????????

ENVIRONEX INTERNATIONAL

T: +61 8 9302 4000 E : sales@environex.net.au

F: +61 8 9302 5000 W: www.environex.net.au

FREE 1800 999 196 19 Motivation Drive, Wangara, WA 6065