

TECHNICAL BULLETIN



19 Motivation Dve Wangara, WA, 6065 AUSTRALIA
T +61 8 9302 4000 | FREE 1800 999 196 | F +61 8 9302 5000

BW5354

Boiler Antifoam

Product Description

ENVIRONEX BW5354 Boiler Antifoam will prevent problems associated with foaming in boilers caused by hydrocarbon contamination and will also allow running at higher cycles.

Product Features.

- Prevent foaming caused by contamination.
- Control foaming caused by increased TDS, SS and Alkalinity
- FDA Approved

Product Benefits

- Prevent condensate contamination due to carry-over
- Allows higher cycles, thereby:
 - Decrease water consumption
 - Reduce energy costs
 - Lower chemical usage
- Ready to use liquid

Application

BW5354 can be used in all boilers where foaming is suspected or where energy savings is sought.

Dosage requirements

- Dose 1-500 ppm BW5354 based on Feed water flow rate.
- Dosage will vary based on feed water quality.

Monitoring

- Monitor steam quality to ensure no carry-over

Handling and Storage.

- Read the label and Material Safety Data Sheet for complete handling information before using this product.
- BW5354 may be stored up to one year.

Quality

- ENVIRONEX International is licensed as a Quality Endorsed Manufacturing Company under ISO9001.