

TECHNICAL BULLETIN



19 Motivation Dve Wangara, WA, 6065 AUSTRALIA
T +61 8 9302 4000 | FREE 1800 999 196 | F +61 8 9302 5000

Page 1 of 2

Date of Issue: 4/4/2016

Last revision: February 2016

File C:\Users\Conrado Concepcion\AppData\Local\Temp\WordHelper\CW6265 - Cooling water antiscalent.docx












CW6265

Cooling Water Antiscalant

Product Description

ENVIRONEX CW6265 Cooling Water Antiscalant is based on revolutionary TERPOLYMER science combined with world-class dispersants in one formulation.



Product Benefits.

-  Superior scale inhibition
-  Excellent calcium tolerance
-  Thermally stable,
-  Effective calcium carbonate dispersant
-  Enhanced calcium sulfate control
-  Inhibits the precipitation of calcium phosphate and calcium phosphonate
-  Stabilizes the reaction products of iron and calcium.
-  All organic.
-  pH Stable
-  Contains no heavy metals
-  Prevents under deposit corrosion



Application

CW6265 can be used in all open recirculation cooling water systems.


Features

-  **CW6265** is compatible with Oxidizing and Non-oxidizing Biocides
-  Ready to use liquid



Dosage requirements

-  Dosage will vary from 2-100 ppm **CW6265** depending on feed water quality.
-  Combine with a good microbial and corrosion control program.


Monitoring

-  Monitoring parameters will vary depending on water quality and system requirements. Consult your **ENVIRONEX** representative for advice on monitoring parameters for your system.

Handling and Storage.

-  Read the label and Material Safety Data Sheet for complete handling information before using this product.
-  **CW6265** may be stored up to one year.

Quality

-  **ENVIRONEX International** is licensed as a Quality Endorsed

TECHNICAL BULLETIN



19 Motivation Dve Wangara, WA, 6065 AUSTRALIA
T +61 8 9302 4000 | FREE 1800 999 196 | F +61 8 9302 5000

Page 2 of 2

Date of Issue: 4/4/2016

Last revision: February 2016

File C:\Users\Conrado Concepcion\AppData\Local\Temp\WordHelper\CW6265 - Cooling water antiscalent.docx

Manufacturing Company under

ISO9001.

CW6265

Contains <10% polymaleic acid copolymer

WARNING

May be corrosive to metals

Causes skin irritation

Causes serious eye irritation

Wear protective gloves/ eye protection/face protection.

IF ON SKIN: Take off contaminated clothing and wash before reuse. Wash with plenty of soap and water.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin or eye irritation occurs: Get medical advice/attention.


Additional information is listed in the Safety Data Sheet

CW3394 is an open recirculation cooling water corrosion inhibitor.

DIRECTIONS: Dosage will vary from 2-100 ppm. CW6265 depending on feed water quality. Combine with a good microbial and corrosion control program.



BATCH No. ??????????



CONTENTS ???? L

ENVIRONEX INTERNATIONAL

T: +61 8 9302 4000 E : sales@environex.net.au

F: +61 8 9302 5000 W: www.environex.net.au

FREE 1800 999 196 19 Motivation Drive, Wangara, WA 6065