

# TECHNICAL BULLETIN



19 Motivation Dve Wangara, WA, 6065 AUSTRALIA  
T +61 8 9302 4000 | FREE 1800 999 196 | F +61 8 9302 5000

## CLEANVAP CIP

### MATERIAL & FUNCTION

CLEANVAP CIP is a heavy duty Potassium Hydroxide based cleaning solution. It is specially formulated for the single stage in-place cleaning of heat modified or high calcium deposits in the food and beverage industry. The use of CLEANVAP CIP is also ideal for plant cleaning by CIP methods in hard water situations and especially useful where sodium content is an issue in effluent water.

CLEANVAP CIP has the added advantage of being sodium free which makes it ideal when plant effluent is used for field irrigation.

### APPLICATION

**H.T.S.T., UHT, EVAPORATORS:** The use concentration will vary with the length of the production run and the hardness of the cleaning water but usually falls in the range of 1.0-3.0% v/v. Circulation times are in the region of 40 minutes at 70-82°C.

**WINE and BEVERAGE INDUSTRY:** Usual concentration is 0.5 – 2.0% v/v at 70 – 80°C. The high level of sequestering and wetting agents helps reduce the frequency of Acid Cleaning

**CHEESE MAKING EQUIPMENT:** Ideal for soils high in calcium and protein. CLEANVAP CIP can be used at 1-2%v/v at 70-85°C and reduce acid cleaning cycles to once per week. Cleaning and rinse times can also be reduced due to superior wetting and rinsing ability.

**BULK MILK TANKERS, RAW & FINISHED MILK TANKS, SILOS & PIPELINES - Circulate** a 1.0-2.0% v/v Solution of CLEANVAP CIP at 70-80°C for 15-30 minutes. No acid step is required.

**CONTROL & DOSE** - Equipment is available for controlling and monitoring CLEANVAP CIP solutions.

### PACKAGING

15, 200 & 1000 Litre containers

### IMPORTANT NOTICE TO CUSTOMER

*Since the use of this product is beyond the control of either seller or manufacturer, their only obligation shall be to replace any quantity of product which is proven defective. They cannot assume any risk or liability in excess of the purchase price of the product itself, which does not include labour or any consequential damages resulting from the use of this product. Determining the suitability of this product for any intended use shall be solely the responsibility of the user. ALWAYS TEST FIRST.*

