

TECHNICAL BULLETIN



19 Motivation Dve Wangara, WA, 6065 AUSTRALIA
T +61 8 9302 4000 | FREE 1800 999 196 | F +61 8 9302 5000

CLEAR SEAL

MATERIAL & FUNCTION

CLEARSEAL is a water-based silicate sealer designed for use as a water repeller on masonry surfaces. CLEARSEAL will assist in the prevention of moss and mould build-up. It can also be used as a pre-seal or pre-grout treatment for very porous surfaces such as terracotta or sandstone. This will greatly assist in the cleanup of excess grout. It is particularly well suited for use around swimming pools where water marks can be a problem. For single leaf masonry brick walls spray application will reduce or prevent migration of water to inside of the wall.

DIRECTIONS FOR USE:

CLEARSEAL should be applied when the surface is clean and dry. Grease, oil or dirt will interfere with the effectiveness of the sealing or pre-sealing process. A lambswool applicator or sprayer (garden) will give best results THIS PRODUCT IS A ONE COAT ONLY APPLICATION. APPLYING TOO MUCH PRODUCT WILL RESULT IN A WHITE RESIDUE THAT IS DIFFICULT TO REMOVE. Apply enough product to soak into the surface. Excess product in the form of pools should be removed immediately. Allow 6 hours curing time – overnight if being used as a pre seal. KEEP WELL AWAY FROM ALUMINIUM, STEEL AND TIMBER SURFACES.

Coverage is typically 12 m²/litre, but may vary from 8 m²/litre for very porous surfaces or tiles to 16 m²/litre for very dense surfaces or tiles.

CLEANUP: Cleanup is in water.

MAINTENANCE: Block walls sealed with CLEARSEAL should be cleaned using Klen REFRESH or MAESTRO if there is a moss or mould problem.

RECOATING should be done every 2 years or when water repellency has ceased.

SAFETY

STRONGLY ALKALINE. R35 Causes severe burns. Avoid contact with skin and eyes. S37/39 Wear suitable gloves and eye/face protections.

PACKAGING

1 Litre, 5 Litre, 15 Litre & 200 Litre containers

IMPORTANT NOTICE TO CUSTOMER

Since the use of this product is beyond the control of either seller or manufacturer, their only obligation shall be to replace any quantity of product which is proven defective. They cannot assume any risk or

*liability in excess of the purchase price of the product itself, which does not include labour or any consequential damages resulting from the use of this product. Determining the suitability of this product for any intended use shall be solely the responsibility of the user. **ALWAYS TEST FIRST.***

KLEN INTERNATIONAL (74) Pty Ltd

T +61 (0)8 9302 4000 F +61 (0)8 9302 5000 TF 1800 999 196

E info@klen.com.au W www.klen.com.au

