

TECHNICAL BULLETIN



19 Motivation Dve Wangara, WA, 6065 AUSTRALIA
T +61 8 9302 4000 | FREE 1800 999 196 | F +61 8 9302 5000

CLEARWATER

MATERIAL & FUNCTION

CLEARWATER is a naturally occurring tannin extract that can be used to clarify turbid water such as that found in dams and bores.

CLEARWATER offers the unique characteristics of being a natural product that will work in most cases without the need to alter pH of the treated water. The flocculant that is formed is typically brown in colour and will usually settle out over a period of several hours. It is important to provide an initial reaction time of 5 to 30 minutes when waters are only slightly turbid as the flocculant may not be readily visible to the naked eye.

APPLICATION

Application rates will vary depending on the cause of turbidity and the degree of contamination.

Most conditions will be treated at a rate of 50 to 300 mls per 1000 litres of water.

CLEARWATER should be added to the water to be treated and, where possible, thoroughly mixed. After addition, allow the treated water to stand for approximately 12 hours before filtering or decanting.

STORAGE

CLEARWATER is a non-hazardous product and may be stored indefinitely. If stored for long periods agitate the container prior to use.

PACKAGING

15 & 200 L drums

IMPORTANT NOTICE TO CUSTOMER

*Since the use of this product is beyond the control of either seller or manufacturer, their only obligation shall be to replace any quantity of product that is proven defective. They cannot assume any risk or liability in excess of the purchase price of the product itself, which does not include labour or any consequential damages resulting from the use of this product. Determining the suitability of this product for any intended use shall be solely the responsibility of the user. **ALWAYS TEST FIRST.***