

TECHNICAL BULLETIN



19 Motivation Drive Wangara, WA, 6065 AUSTRALIA
T +61 8 9302 4000 | FREE 1800 999 196 | F +61 8 9302 5000

ENDURE

The image shows a detailed product label for ENDURE sealer. It features a red and white hazard warning section on the left with symbols for 'Flammable Liquid' (3) and 'Poison'. The central part of the label includes a photograph of a masonry surface being treated with the sealer. To the right of the photo, there is a detailed text block containing application instructions, coverage information, and safety warnings. The bottom of the label includes barcode information for different container sizes (1L, 4L, 20L, 200L) and contact details for EnviroNex International.

MATERIAL & FUNCTION

ENDURE is a unique blend of acrylic resins formulated especially for application to most masonry surfaces. **ENDURE** highlights the natural colours and texture of the surface and provides protection against wear and staining.

APPLICATION

Ensure the surface is thoroughly dry. The surface should have been left absolutely clean. Should the surface require cleaning prior to sealing, a further drying period of 2 - 3 days should be allowed. **DO NOT USE SPIRITS OF SALTS/HYDROCHLORIC ACID ON SLATE SURFACES.**

Newly laid pavers or stone surfaces should be left to dry for ~14 days prior to sealing.

Apply one thin coat of **ENDURE** evenly using a brush, heavy duty sprayer or lambswool applicator ensuring no bubbles are trapped in the sealer. **DO NOT USE A ROLLER.** Allow to dry overnight. 1 litre of **ENDURE** will cover approximately 7 - 15 sq metres per coat depending on the porosity of the surface being treated. At least 2 coats of sealer are recommended for normal domestic use, allow at least up to 8 hours between coats (depending on ambient conditions) and 24 hours before heavy traffic. Depending on the porosity of the surface and the desired level of gloss, additional coats may be applied. (Note: A glossier finish may tend to accentuate scratch marks.) Avoid walking on the floor for 12 hours after final coat. Brushes may be cleaned in **CYCLONE**.

RETREATMENT

Depending on the extent of traffic, your floor may require resealing with **ENDURE** to remove scratching and scuff marks. This will bring your floor back to its original condition. Follow original sealing instructions. If the surface has been previously sealed with a polyurethane sealer, this must be completely removed using the appropriate paint stripper.

Resealing is required after approximately 12 - 24 months inside and 12 monthly outside depending on the amount of wear due to traffic, weathering and cleaning.

CAUTION

This product is highly flammable. Ensure adequate ventilation and no naked flames or smoking. Avoid contact with skin and eyes and avoid breathing vapour or spray mist.

PACKAGING

2, 10, 20 & 200 Litre containers

IMPORTANT NOTICE TO CUSTOMER

*Since the use of this product is beyond the control of either seller or manufacturer, their only obligation shall be to replace any quantity of product which is proven defective. They cannot assume any risk or liability in excess of the purchase price of the product itself, which does not include labour or any consequential damages resulting from the use of this product. Determining the suitability of this product for any intended use shall be solely the responsibility of the user. **ALWAYS TEST FIRST***