

TECHNICAL BULLETIN



19 Motivation Dve Wangara, WA, 6065 AUSTRALIA
T +61 8 9302 4000 | FREE 1800 999 196 | F +61 8 9302 5000

ENHANCE

SEALS & BEAUTIFIES STONE

MATERIAL & FUNCTION

ENHANCE is a solvent based sealer system used to bring out the colour in dull or lifeless stone, particularly limestone. The more coats applied, the more shine is obtained. ENHANCE protects against soiling and staining.. ENHANCE is a solvent-based solution of acrylic (methacrylate) resin co-polymers and provides protection against the penetration of stains, vegetable oils, grease etc. It allows for easier cleaning as well as adding depth and sharpness to the colours by imparting a "wet look" finish. It will also provide a seal against water in wet or damp applications such as around swimming pools, and it resists the emergence of efflorescence.

USES

ENHANCE finds its main use in sealing of stone, particularly limestone. ENHANCE can be used both internally or externally and has the benefit of not being subject to yellowing.

APPLICATION

Ensure the surface is totally clean and dry. All paint, oil, grease, efflorescence and any other foreign matter must be removed. Older surfaces, which have weathered and discoloured should be hosed down and scrubbed again with clean water to remove all residues of acid and waste. Allow to dry for at least 24 hours. ENHANCE should be applied using a soft bristle brush, lambswool applicator, broom or squeegee. **DO NOT USE A ROLLER AS THIS CREATES BUBBLES AND WEAKNESSES IN THE FILM.**

It is recommended that at least three coats be applied, allowing not less than 4 hours between coats. Full curing takes up to 48 hours depending on ambient weather conditions, and traffic should be restricted as much as possible during this period. Usage rate varies according to the porosity of the surface being treated, however, generally a coverage of 10 - 12 square metres per litre per application is achievable. Brushes will clean in lacquer thinner, acetone or xylol.

CAUTION

Avoid contact with skin and eyes and avoid breathing vapour or spray mist.

Ensure NO SMOKING or NAKED FLAME during application of sealer and provide ADEQUATE VENTILATION.

PACKAGING

1 Litre, 4 Litre, 10 Litre, 20 Litre & 200 Litre containers

IMPORTANT NOTICE TO CUSTOMER

Since the use of this product is beyond the control of either seller or manufacturer, their only obligation shall be to replace any quantity of product, which is proven defective. They cannot assume any risk or liability in excess of the purchase price of the product itself, which does not include labour or any consequential damages resulting from the use of this product. Determining the suitability of this product for any intended use shall be solely the responsibility of the user. ALWAYS TEST FIRST

