

# TECHNICAL BULLETIN



19 Motivation Drive Wangara, WA, 6065 AUSTRALIA  
T +61 8 9302 4000 | FREE 1800 999 196 | F +61 8 9302 5000

## ENHANCER PLUS

### SEALS & BEAUTIFIES STONE

#### MATERIAL & FUNCTION

**ENHANCER PLUS** is a solvent based sealer system used to bring out the colour in dull or lifeless stone, particularly limestone. The more coats applied, the more shine is obtained. **ENHANCER PLUS** protects against soiling and staining.. **ENHANCER PLUS** is a solvent-based solution of acrylic (methacrylate) resin co-polymers and provides protection against the penetration of stains, vegetable oils, grease etc. It allows for easier cleaning as well as adding depth and sharpness to the colours by imparting a "wet look" finish. It will also provide a seal against water in wet or damp applications such as around swimming pools, and it resists the emergence of efflorescence.

#### USES

**ENHANCER PLUS** finds its main use in sealing of stone, particularly limestone. **ENHANCER PLUS** can be used internally or externally and has the benefit of not being subject to yellowing.

#### APPLICATION

**Ensure the surface is totally clean and dry.** All paint, oil, grease, efflorescence and any other foreign matter must be removed. Older surfaces, which have weathered and discoloured should be hosed down and scrubbed again with clean water to remove all residues of acid and waste. Allow to dry for at least 24 hours. **ENHANCER PLUS** should be applied using a soft bristle brush, lambswool applicator, broom or squeegee. **DO NOT USE A ROLLER AS THIS CREATES BUBBLES AND WEAKNESSES IN THE FILM.**

It is recommended that at least three coats be applied, allowing not less than 4 hours between coats. Full curing takes up to 48 hours depending on ambient weather conditions, and traffic should be restricted as much as possible during this period. Usage rate varies according to the porosity of the surface being treated, however, generally a coverage of 10 - 12 square metres per litre per application is achievable. Brushes will clean in lacquer thinner, acetone or xylene.

#### CAUTION

*Avoid contact with skin and eyes and avoid breathing vapour or spray mist.*

*Ensure NO SMOKING or NAKED FLAME during application of sealer and provide ADEQUATE VENTILATION.*

#### PACKAGING

2 Litre, 10 Litre, 20 Litre & 200 Litre containers

#### IMPORTANT NOTICE TO CUSTOMER

*Since the use of this product is beyond the control of either seller or manufacturer, their only obligation shall be to replace any quantity of product, which is proven defective. They cannot assume any risk or liability in excess of the purchase price of the product itself, which does not include labour or any consequential damages resulting from the use of this product. Determining the suitability of this product for any intended use shall be solely the responsibility of the user. **ALWAYS TEST FIRST.***

