

TECHNICAL BULLETIN



19 Motivation Dve Wangara, WA, 6065 AUSTRALIA
T +61 8 9302 4000 | FREE 1800 999 196 | F +61 8 9302 5000

ENVIROFORM

Form Release Agent

MATERIAL & FUNCTION

ENVIROFORM prevents adhesion of concrete to formwork and concrete handling equipment. ENVIROFORM reduces surface adhesion of concrete forms and produces good quality off-form concrete.

ENVIROFORM reacts with the alkali present in the cement to form a microscopic water repellent film between concrete and formwork. By this action, formwork is protected against continuous wetting and drying action.

APPLICATION

ENVIROFORM may be sprayed or brush applied to all contact surfaces of formwork at the rate of 6-18 square metres/litre. It finds application for prevention of cement sticking to kibbles, wheelbarrows, shovels and tools of trade.

NOTES

ENVIROFORM may be used on aluminium or steel frames to protect against splashes of concrete or mortar.

LIMITATIONS

When ENVIROFORM is used for form release work and ENVIROCURE 1951 is to be used, care must be taken to thoroughly clean down concrete surface removing all traces of very fine powder residue prior to the application of ENVIROCURE 1951. The powder itself is fully compatible with renders and paints.

PACKAGING

20 & 200 Litre containers

IMPORTANT NOTICE TO CUSTOMER

*Since the use of this product is beyond the control of either seller or manufacturer, their only obligation shall be to replace any quantity of product which is proven defective. They cannot assume any risk or liability in excess of the purchase price of the product itself, which does not include labour or any consequential damages resulting from the use of this product. Determining the suitability of this product for any intended use shall be solely the responsibility of the user. **ALWAYS TEST FIRST.***

F:\TECHBULL\Enviroform.DOC.