

TECHNICAL BULLETIN



19 Motivation Dve, Wangara, WA, 6065 AUSTRALIA
T +61 8 9302 4000 | FREE 1800 999 196 | F +61 8 9302 5000

HYDRO C - HOOK OIL (SOLVENT TYPE HOOK OIL)

MATERIAL & FUNCTION

HYDRO C - HOOK OIL is a solvent based product designed as a dewatering oil, and rust preventative for hooks and rollers in abattoirs and other meat establishments.

FEATURES

Effectively lubricates hooks and rollers. Protects against rusting. Does not build up or form hard surface coatings and remains easy to clean and maintain.

APPEARANCE

Clear to light yellow liquid.

APPLICATION

Use neat in a 200L to 400L holding tank. Dip the basket full of cast iron or s/s hooks in for approximately 1 minute to 10 minutes depending on the state of the hooks. Make sure a thorough rinse in warm to hot water is done after the acid stage and before the oil stage.

PERFORMANCE CHARACTERISTICS

This product is intended to be applied to hooks after the cleaning process to leave a thin film of oil which reduces surface rusting. It is not intended for direct contact with food product but may incur incidental contact.

TYPICAL ANALYSIS

Density @ 15 ^o C	0.8
Flash Point COC °C	40

PACKAGING

20 Litre metal can & 200 Litre Plastic Mauser.

IMPORTANT NOTICE TO CUSTOMER

*Since the use of this product is beyond the control of either seller or manufacturer, their only obligation shall be to replace any quantity of product, which is proven defective. They cannot assume any risk or liability in excess of the purchase price of the product itself, which does not include labour or any consequential damages resulting from the use of this product. Determining the suitability of this product for any intended use shall be solely the responsibility of the user. **ALWAYS TEST FIRST.***

TECHNICAL BULLETIN



19 Motivation Dve, Wangara, WA, 6065 AUSTRALIA
T +61 8 9302 4000 | FREE 1800 999 196 | F +61 8 9302 5000

Technical Bulletin for the application of HYDRO C - HOOK OIL to meat hooks in Abattoirs and Butchers

