

TECHNICAL BULLETIN



19 Motivation Dve, Wangara, WA, 6065 AUSTRALIA
T +61 8 9302 4000 | FREE 1800 999 196 | F +61 8 9302 5000

OMEGA **NON FOAMING CLEANER** **- ALUMINIUM SAFE -**

MATERIAL & FUNCTION

OMEGA is a metasilicate-based liquid non foaming, alkaline, biodegradable cleaner specifically designed for circulation-in-place equipment where soft metals (particularly aluminium) are exposed.

OMEGA is formulated to handle water hardness levels exceeding 800mg/L. It will quickly and effectively dissolve and emulsify soils, remove fats and protein from all surfaces, thus reducing the potential of bacterial growth. **OMEGA** contains sequestering agents to control scale formation from hard water supply.

APPLICATION

Dilute **OMEGA** at the rate of 6 ml per litre in water with a temperature of 60°C in the cleaning system.

CAUTION

This product is alkaline. Avoid contact with skin and eyes.

PACKAGING

15 Litre , 200 Litre & 1000 Litre containers.

IMPORTANT NOTICE TO CUSTOMER

*Since the use of this product is beyond the control of either seller or manufacturer, their only obligation shall be to replace any quantity of product which is proven defective. They cannot assume any risk or liability in excess of the purchase price of the product itself, which does not include labour or any consequential damages resulting from the use of this product. Determining the suitability of this product for any intended use shall be solely the responsibility of the user. **ALWAYS TEST FIRST.***