

TECHNICAL BULLETIN



19 Motivation Dve Wangara, WA, 6065 AUSTRALIA
T +61 8 9302 4000 | FREE 1800 999 196 | F +61 8 9302 5000

DAIRY HYGIENE SYSTEMS

ACID BOSS

LIQUID ACIDIC DETERGENT

MATERIAL & FUNCTION

ACID BOSS is a highly concentrated acidic detergent formulated for CIP applications, descaling of stainless steel surfaces and removal of mineral deposits in food and beverage processing equipment. **ACID BOSS** is formulated for “worst case” conditions where excessively hard water or high levels of scale build up are encountered.

APPLICATION

Solutions of **ACID BOSS** are passed through equipment such as milking machines, tanks, vats heat exchangers and pasteurisers etc, as required to remove mineral deposits. It is generally used in conjunction with an alkali cleaner such as **CIP KLEN** or **DAIRY KLEN**. **SOLO PLUS** is recommended in excessively hard water conditions. Dilute **ACID BOSS** between 2 to 3 mLs per Litre of water at 65°C to 85°C and re-circulate for descaling of milk lines, machines & equipment.

DIRECTIONS FOR USE

Apply **ACID BOSS** at a dilution of 2 to 5 mLs per Litre depending on degree of scaling and water conditions. Best results are obtained at 65 C to 85 C. Re-circulate solution for 5 to 7 minutes before draining equipment and rinsing with clean water

CAUTION: Do not exceed manufacturers' maximum temperature recommendations when cleaning cooling vessels such as milk vats.

SAFETY INSTRUCTIONS

ACID BOSS is highly acidic and contact with skin should be avoided. If splashed, thoroughly wash skin with water and remove contaminated clothing. If in eye, flush under running water for 15 minutes. If swallowed give water to drink and contact a Doctor or Poison information centre. Do not induce vomiting.

PACKAGING

5 Litre, 15 Litre 120 Litre & 200 Litre containers.

IMPORTANT NOTICE TO CUSTOMER

*Since the use of this product is beyond the control of either seller or manufacturer, their only obligation shall be to replace any quantity of product that is proven defective. They cannot assume any risk or liability in excess of the purchase price of the product itself, which does not include labour or any consequential damages resulting from the use of this product. Determining the suitability of this product for any intended use shall be solely the responsibility of the user. **ALWAYS TEST FIRST.***