

# TECHNICAL BULLETIN



19 Motivation Dve Wangara, WA, 6065 AUSTRALIA  
T +61 8 9302 4000 | **FREE** 1800 999 196 | F +61 8 9302 5000

## CW3213

### Closed Loop Cooling Water Corrosion Inhibitor Product Description

**ENVIRONEX CW3213** Closed Loop Corrosion inhibitor is a nitrite-based, red colored, liquid. It is designed to control corrosion in ferrous metal systems and ferrous metal systems containing yellow metals.

#### Product Benefits.

- Eliminates corrosion in closed cooling water systems
- Easy to use
- Easy to detect leaks
- Cost effective
- Extremely low maintenance
- Indicator build in.
- Stops Copper corrosion

#### Application

**ENVIRONEX CW3213** can be used in all closed loop cooling systems and chiller systems.

#### Features

- ENVIRONEX CW3213** is compatible with Glycol based antifreeze products.
- Red color makes it easy to detect leaks and monitor activity.
- Ready to use liquid

#### Dosage requirements

- Dose 1 liter of **ENVIRONEX CW3213** per 30 liters of system volume.
- Add non-oxidizing biocide. E.g. **ENVIRONEX CW1317**.

#### Monitoring

- Control Nitrite Levels between 1000 and 2000ppm and Azole levels at 20-100ppm.

#### Handling and Storage.

- Read the label and Material Safety Data Sheet for complete handling information before using this product.
- CW3213** may be stored up to one year.

#### Quality

- ENVIRONEX International** is licensed as a Quality Endorsed Manufacturing Company under ISO9001.

# TECHNICAL BULLETIN



19 Motivation Dve Wangara, WA, 6065 AUSTRALIA  
T +61 8 9302 4000 | **FREE** 1800 999 196 | F +61 8 9302 5000

## CW3213

Contains 6 g/L SODIUM HYDROXIDE, 100 g/L SODIUM NITRITE

### DANGER

**Toxic if swallowed. Causes skin irritation. Causes serious eye irritation**

**Very toxic to aquatic life**


Wear protective gloves/ protective clothing/ eye protection/face protection. IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER or doctor/physician. IF ON SKIN: Wash with plenty of soap and water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin or eye irritation occurs: Get medical advice/attention.

CW3213 is for use as a cooling water rust inhibitor for ferrous metals

Directions: Add 1 litre CW3213 to 30 litres of water.



BATCH NO. ??????????



CONTENTS ???? L

ENVIRONEX INTERNATIONAL

T: +61 8 9302 4000 E : sales@environex.net.au

F: +61 8 9302 5000 W: www.environex.net.au

FREE 1800 999 196 19 Motivation Drive, Wangara, WA 6065



created by free version of

**DocuFreezer**