

TECHNICAL BULLETIN



19 Motivation Drive, Wangara, WA, 6065 AUSTRALIA
T +61 8 9302 4000 | FREE 1800 999 196 | F +61 8 9302 5000

GRAFFITI CLEAN 400 ONE STEP GRAFFITI REMOVAL

MATERIAL & FUNCTION

GRAFFITI CLEAN 400 is a user-friendly organic solvent solution designed to remove certain types of graffiti from all types of building surfaces. **GRAFFITI CLEAN 400** has been specially blended using a wide range of solvents, to produce a product capable of removing graffiti caused by all types of paint, leather dyes and texta pens. This product is very effective at paint removal where graffiti is on a pre-painted surface; some of this paint coating will be removed, along with the graffiti. **GRAFFITI CLEAN 400** acts very quickly and has a fast evaporation rate which is of value in enclosed spaces or occupied areas in buildings where customers are present.

APPLICATION

The method of application depends on the type of surface, size and nature of the graffiti and how long the graffiti has been *in situ*, eg. graffiti which has been on the surface for some time will be harder to remove than graffiti that has not cured or has not been baked by the sun. Ideally removal should occur within 24 hours.

For areas under 10 square metres - apply **GRAFFITI CLEAN 400** by stiff bristle brush or spray container and leave **GRAFFITI CLEAN 400** in contact for 15 seconds. Apply more **GRAFFITI CLEAN 400** in the same manner, repeating the process if necessary. As the graffiti breaks down it is essential that copious quantities of water containing household detergent at a rate of 10 : 1 are used to wash off the residue immediately. For heavily coated areas or areas that have been subjected to baking by the sun, the process may need to be repeated. **GRAFFITI CLEAN 400** may not be totally effective on all graffiti as experimentation by the 'community artists' produces new 'cocktails' continually. In these cases it is recommended that **CITRONEX** be used. Apply **CITRONEX** using a paint brush, leave for 5 minutes and then apply a second coat in the same manner. As the graffiti breaks down use copious quantities of water containing **S 21 M P C** 10:1 to wash off the residue immediately.

For areas over 10 square metres - it may be cost effective when rinsing to utilize airless spray equipment for larger areas. In these cases it is recommended that the vehicle or trailer hold a drum of water with **S 21 M P C** added at a rate of 10:1. Apply **GRAFFITI CLEAN 400** by brush as for smaller areas. With the breakdown of the graffiti, hose off using spray nozzle on low pressure and a stiff bristle brush to assist in removal. If residual is left repeat process. If using **CITRONEX** the application process is the same, only contact time should be extended to 5 minutes before removal.

Remember an application of **GRAFFITI CLEAN 400** by brush may assist the **CITRONEX**-removal process at this stage.

NOTE

We recommend regular removal processes are undertaken rather than allowing the graffiti to build up as the removal process will then be harder and more costly in labour and materials.

GRAFFITI CLEAN representatives are available to provide technical assistance during removal processes.

SAFETY

Ensure adequate ventilation during use. Wear TYPE A full face organic vapour respirator in confined areas. (Ref. Australian Standard 1715 - 1991). Avoid contact with skin and eyes, wear eye protection, Viton or PVA gloves and solvent resistant overalls during use. Refer to the MSDS for further information.

GENERAL DATA

Compound type suspended solvent blends

Volatiles by volume - 100%

Density 1.01 ± 0.02 kg/L

Flash Point L 23°C (closed cup)

Suitable for

Enamel paints - very good

Leather dyes - very good

Acrylic paints - very good

PACKAGING

20 litre and 200 litre containers.

IMPORTANT NOTICE TO CUSTOMER

*Since the use of this product is beyond the control of either seller or manufacturer, their only obligation shall be to replace any quantity of product which is proven defective. They cannot assume any risk or liability in excess of the purchase price of the product itself, which does not include labour or any consequential damages resulting from the use of this product. Determining the suitability of this product for any intended use shall be solely the responsibility of the user. **ALWAYS TEST FIRST.***