

TECHNICAL BULLETIN



19 Motivation Dve, Wangara, WA, 6065 AUSTRALIA
T +61 8 9302 4000 | FREE 1800 999 196 | F +61 8 9302 5000

LC1932

MATERIAL & FUNCTION

LC1932 is a heavy duty low foaming alkaline cleaner designed for use in automatic CIP cleaning systems, for cleaning of equipment such as: Pasteurizers, Concentrators, Cheese Making Machines, Milk Holding Vats and Road Tankers.

LC1932 is based on liquid Sodium Hydroxide

LC1932 DOES NOT CONTAIN CHLORINE.

APPLICATION

LC1932 is recommended to be used between 10 to 40 mL per litre of water, depending on the degree of contamination and at 65°C to 70°C with a circulation time between 10 to 30 minutes. Equipment should be rinsed thoroughly.

CAUSTICITY CHART	PER 100 LITRES OF WATER				
CAUSTICITY, % w/v	0.5%	1%	1.5%	2%	2.5%
KGS OF LC1932	1.6	3.2	4.8	6.3	7.9
LTRS OF LC1932	1.2	2.4	3.5	4.7	5.9

CAUTION

LC1932 is highly caustic and should be handled with care. Avoid contact with the skin, eyes and clothing. Wear goggles and gloves when handling the concentrate product.

FIRST AID

If splashed - remove contaminated clothing and wash thoroughly. If swallowed - contact a doctor or The Poisons Information Centre immediately. Ph 13 1126. DO NOT induce vomiting - give milk or water.

PACKAGING

15 Litre, 200 Litre & 1000 Litre containers.

IMPORTANT NOTICE TO CUSTOMER

Since the use of this product is beyond the control of either seller or manufacturer, their only obligation shall be to replace any quantity of product, which is proven defective. They cannot assume any risk or liability in excess of the purchase price of the product itself, which does not include labour or any consequential damages resulting from the use of this product. Determining the suitability of this product for any intended use shall be solely the responsibility of the user. ALWAYS TEST FIRST.