

# TECHNICAL BULLETIN



19 Motivation Dve, Wangara, WA, 6065 AUSTRALIA  
T +61 8 9302 4000 | FREE 1800 999 196 | F +61 8 9302 5000

## OPUS

### MATERIAL & FUNCTION

**OPUS** is a specially formulated low foaming detergent powder designed for use in stainless steel tanks and lines, for the removal of tartrate, protein, various wine stains and neutralization of food acid residues.

**OPUS** is a non-caustic product and is not classified as a dangerous good under Australian Dangerous Goods Regulations.

**OPUS DOES NOT CONTAIN CHLORINE.**

Areas of use:

- Crushers
- Presses
- Filters
- Lines
- Tanks
- Fermenters
- Packaging equipment
- Barrels

### DIRECTIONS FOR USE:

Dilute **OPUS** at a rate of 2% to 5% (2 to 5 kilograms per 100 litres) depending on the degree of soiling to be removed. Best results are obtained by using **OPUS** in potable water at a temperature of approximately 50°C.

Allow the mixture to circulate through the equipment with a contact time of between 10 to 30 minutes. Longer contact times may be necessary to remove heavy contamination (tartar).

**OPUS** has excellent rinsing properties and complete rinsing can be confirmed by checking the pH of the final rinse water. In most cases a Citric Acid rinse will not be required.

### IMPORTANT NOTICE TO CUSTOMER

*Since the use of this product is beyond the control of either seller or manufacturer, their only obligation shall be to replace any quantity of product, which is proven defective. They cannot assume any risk or liability in excess of the purchase price of the product itself, which does not include labour or any consequential damages resulting from the use of this product. Determining the suitability of this product for any intended use shall be solely the responsibility of the user. **ALWAYS TEST FIRST.***

F:\TECHBULL\Opus.doc.

