

TECHNICAL BULLETIN



19 Motivation Dve Wangara, WA, 6065 AUSTRALIA
T +61 8 9302 4000 | FREE 1800 999 196 | F +61 8 9302 5000

PRESTIGE SURFACE SEALER

UN 1866 RESIN SOLUTION FLAMMABLE
CLASS 3 HAZCHEM 3Y PG III

Xn Harmful, Xi Irritant, R10 Flammable, R20/21 Harmful by inhalation and in contact with the skin, R37/38 Irritating to respiratory system and skin, R65 Harmful; May cause lung damage if swallowed.

FIRST AID: For advice, contact a Poisons Information Centre (Phone Australia 131 126) or a doctor (at once). If swallowed, do NOT induce vomiting. If in eyes, wash out immediately with water. If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water. If inhaled, remove from contaminated area. Apply artificial respiration if not breathing.

SAFETY DIRECTIONS: Avoid contact with skin and eyes. Avoid breathing vapours or spray mist. Apply under well ventilated conditions. Keep container tightly closed in a well ventilated area. S16 Keep away from sources of ignition.

EMERGENCY INFORMATION:
SPILLS: Eliminate ignition sources, S29 Do not empty into drains. Absorb onto earth, vermiculite or other absorbent material. Transfer into clean labelled drums for disposal.
FIRE: S43 In case of fire use sand, earth, chemical powder or foam. Water spray may be used to cool containers.

ENVIROSHIELD COATINGS
19 Motivation Drive, Wangara, WA 6065
Ph: (08) 9302 4000



POISON
KEEP OUT OF REACH OF CHILDREN
READ SAFETY DIRECTIONS BEFORE OPENING OR USING



PRESTIGE SURFACE SEALER

CONTAINS 35-50% Xylene, 35-50% Liquid Hydrocarbons
ENVIROSHIELD COATINGS

Prestige Surface sealer is a unique blend of acrylic resins formulated especially for application to most masonry surfaces to provide a wet look. Allow a minimum of 14 days from date of laying/grouting before application to ensure all moisture has left grout and substrate. Ensure all efflorescence (whitish salts on surface) has ceased to appear (remove residual salts with ANTI EFF, as per label instructions). The surface to be treated should be cleaned free from dust and thoroughly dry. Not suitable for polished, honed, dense or smooth surfaces. Always test first.

DIRECTIONS: Apply using a Viton sprayer or lambswool applicator ensuring no bubbles are trapped in the sealer. Allow to dry overnight. At least 2 coats of sealer are recommended for normal domestic use. Allow 1-4 hrs between coats (depending on ambient conditions) and 24 hrs before heavy traffic. Clean up with Cyclohexane. Resealing should not be required before 24-36 months, potentially longer depending on traffic, weathering and cleaning.

Coverage: 8-12 sq m per litre per coat, depending on porosity. Clean up any spills or soiling material within 2-4 hours.

Additional information is listed in the Material Safety Data Sheet

IN AN EMERGENCY CALL 000
POISON ON FIRE SERVICE

NET CONTENTS

<input type="checkbox"/> 1 L	<input type="checkbox"/> 4 L
<input type="checkbox"/> 10 L	<input type="checkbox"/> 20 L
<input type="checkbox"/> 200 L	



MATERIAL & FUNCTION

PRESTIGE SURFACE SEALER is a unique blend of acrylic resins formulated especially for application to all masonry surfaces. **PRESTIGE SURFACE SEALER** highlights the natural colours and texture of the surface and provides protection against wear and staining.

APPLICATION

Allow a minimum of 14 days from date of laying/grouting before application to ensure all moisture has left grout and substrate. Ensure all efflorescence (whitish salts on surface) has ceased to appear (remove residual salts with **ANTI EFF**, as per label instructions). The surface to be treated should be cleaned free from dust and thoroughly dry.

DIRECTIONS: Apply using a nylon broom, Viton sprayer or lambswool applicator ensuring no bubbles are trapped in the sealer. Allow to dry overnight.

At least 2 coats of sealer are recommended for normal domestic use, allow 1-4 hrs between coats (depending on ambient conditions) and 24 hrs before heavy traffic. Resealing should not be required before 24-36 months, potentially longer depending on traffic, weathering and cleaning.

Coverage: 8-12 sq m per litre per coat, depending on porosity.
Clean up any spills or soiling material within 2-4 hours.

RETREATMENT

Depending on the extent of traffic, your floor may require resealing with **PRESTIGE SURFACE SEALER** to remove scratching and scuff marks. This will bring your floor back to its original condition. Follow original sealing instructions. If the surface has been previously sealed with a polyurethane

TECHNICAL BULLETIN



19 Motivation Dve Wangara, WA, 6065 AUSTRALIA
T +61 8 9302 4000 | FREE 1800 999 196 | F +61 8 9302 5000

sealer, this must be completely removed using the appropriate paint stripper or **CYCLONE**.

Resealing should not be required before 1 - 3 years, potentially longer depending on traffic weathering and cleaning.

CAUTION

This product is highly flammable. Ensure adequate ventilation and no naked flames or smoking. Avoid contact with skin and eyes and avoid breathing vapour or spray mist.

PACKAGING

2, 10, 20 & 200 Litre containers

IMPORTANT NOTICE TO CUSTOMER

*Since the use of this product is beyond the control of either seller or manufacturer, their only obligation shall be to replace any quantity of product which is proven defective. They cannot assume any risk or liability in excess of the purchase price of the product itself, which does not include labour or any consequential damages resulting from the use of this product. Determining the suitability of this product for any intended use shall be solely the responsibility of the user. **ALWAYS TEST FIRST.***

F:\TECHBULL\PrestigeSurfaceSealer.doc